

▼ User Menu



- [Home](#)
- [Manage Accounts](#)
- [Change Password](#)
- [Edit Profile](#)
- [Logout](#)

▼ Submissions Menu



- [Submit Manuscript](#)
- [Display Submitted Manuscripts](#)
- [Display Co-Authored Manuscripts](#)
- [English Editing](#)
- [Discount Vouchers](#)
- [Invoices](#)
- [LaTeX Word Count](#)

▼ Reviewers Menu



- [Reviews](#)
- [Volunteer Preferences](#)

Manuscript Information Overview

Manuscript ID	applsci-2368145
Status	Pending editor decision
Article type	Article
Title	Investigating the acid- and enzyme-induced coagulation of raw milk by dielectric and rheological measurements
Journal	<i>Applied Sciences</i>
Section	Food Science and Technology
Abstract	In this study, the enzyme-induced and acid coagulation of raw milk samples were investigated, and these two processes were monitored by determining the changes in dielectric and rheological behavior to see if any correlations can be found between these two properties. For the enzyme-induced experiments, 250 cm³ of raw milk sample and industrial chymosin was used, and during the acid coagulation, industrial thermophile yogurt culture was added to the same amount of milk. The apparent viscosity was monitored with a vibro viscometer, and for the determination of the dielectric constant, an open-ended dielectric assessment kit connected to a vector network analyzer was being used. Our experimental findings revealed that during both enzyme-induced and acid coagulation, two distinct phases can be found in terms of dielectric and rheological properties, and regardless of the molecular mechanisms behind the aggregation of casein micelles, a strong correlation can be found between the extent of apparent viscosity and dielectric constant, suggesting that dielectric measurements might be adequately used in these dairy processing technologies. These results verified the applicability of the non-destructive dielectric measurements in dairy technologies.
Keywords	acid coagulation, enzyme-induced coagulation, dielectric properties, clot formation, rheological properties
Manuscript File	manuscript.docx
PDF File	manuscript.pdf

Author Information

Submitting Author	Zoltán Jákói
Corresponding Author	Zoltán Péter Jákói
Author #1	Réka Dobozi
E-Mail	dobozireka@mk.u-szeged.hu (co-author email will be published)
Author #2	Zoltán Péter Jákói
E-Mail	jakoiz@mk.u-szeged.hu (corresponding author email)
Author #3	Csanádi József
E-Mail	csanadi@mk.u-szeged.hu (co-author email will be published)
Author #4	Sándor Beszédes
E-Mail	beszedes@mk.u-szeged.hu (co-author email will be published)

Manuscript Information

Received Date	11 April 2023
Revised Date	5 May 2023
Submission to First Decision (Days)	28
Submission to Publication (Days)	
Round of Revision	2
Word Count	4076
Page Count	11

Review Report

Reviewer 1	Review Report (Round 1)		
Reviewer 2	Review Report (Round 1)	Review Report (Round 2)	
Reviewer 3	Review Report (Round 1)		
Reviewer 4	Review Report (Round 1)	Review Report (Round 2)	
Reviewer 5	Review Report (Round 1)	Review Report (Round 2)	Review Report (Round 3)
Reviewer 6	Review Report (Round 1)	Review Report (Round 2)	

Investigating the acid- and enzyme-induced coagulation of raw milk by dielectric and rheological measurements

Réka Dobozi ¹, Zoltán Jákó ^{2*}, József Csanádi ¹ and Sándor Beszedes ²

¹ Department of Food Engineering, Faculty of Engineering, University of Szeged, H-6725 Szeged, Hungary; dobozireka@mk.u-szeged.hu (R.D.), csanadi@mk.u-szeged.hu (J.C)

² Department of Biosystems Engineering, Faculty of Engineering, University of Szeged, H-6725 Szeged, Hungary; beszedes@mk.u-szeged.hu (S.B.); jakoiz@mk.u-szeged.hu (Z.J)

* Correspondence: jakoiz@mk.u-szeged.hu (Z.J); Tel.: +3662-546-037

Abstract: In this study, the enzyme-induced and acid coagulation of raw milk samples were investigated, and these two processes were monitored by determining the changes in dielectric and rheological behavior to see if any correlations can be found between these two properties. For the enzyme-induced experiments, 250 cm³ of raw milk sample and industrial chymosin was used, and during the acid coagulation, industrial thermophile yogurt culture was added to the same amount of milk. The apparent viscosity was monitored with a vibro viscometer, and the dielectric constant was measured in a frequency range of 200–2400 MHz with an open-ended dielectric assessment kit (DAK) connected to a vector network analyzer (VNA). Our experimental findings revealed that during both enzyme-induced and acid coagulation, two distinct phases can be found in terms of dielectric and rheological properties, and regardless of the molecular mechanisms behind the aggregation of casein micelles, a strong correlation (with R²-values ranging between 0,967–0,992) can be found between the extent of apparent viscosity and dielectric constant, suggesting that dielectric measurements might be adequately used in these dairy processing technologies. These results verified the applicability of the non-destructive dielectric measurements in dairy technologies.

Keywords: acid coagulation, enzyme-induced coagulation, dielectric properties, clot formation, rheological properties

1. Introduction

Milk coagulation is a complex process that plays a crucial role in the production of various dairy products, such as cheese and yogurt. The coagulation of milk is primarily induced by two mechanisms: enzymatic and acid coagulation. Enzyme-induced coagulation occurs when enzymes, such as rennet or pure chymosin, break down the casein micelles, leading to the formation of a protein network [1]. In contrast, acid coagulation is triggered by the reduction of milk's pH, which destabilizes the casein micelles and leads to aggregation and subsequent network formation [2]. Both processes result in a gel-like structure, which ultimately forms the basis of numerous dairy products.

Understanding the changes in the physical properties of milk during coagulation is essential for optimizing the manufacturing processes and ensuring the quality and consistency of the final products. Among various physical properties, dielectric and rheological properties have been widely investigated to provide insights into the changes in the protein network structure and the overall behavior of milk during coagulation [3,4]. Dielectric properties are related to the electrical characteristics of milk samples and can provide information on the molecular interactions and the evolution of the protein network [5]. Rheological properties, on the other hand, pertain to the flow and deformation behavior of milk, which can be used to study the changes in viscosity, elasticity, and gel strength during the coagulation process [6].

Citation: To be added by editorial staff during production.

Academic Editor: Firstname Last-name

Received: date

Revised: date

Accepted: date

Published: date



Copyright: © 2023 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

Milk is a complex colloidal system containing fat globules, protein fractions, carbohydrates, enzymes, vitamins, and inorganic components such as salts. Therefore, the development of accurate and rapid detection methods for quantifying the dispersed components and their size distribution is of great significance, not only for scientific purposes but also for practical applications. For example, photon correlation spectroscopy is a suitable method for determining the composition of the dispersed phase of colloidal systems, and it only takes a few minutes [7]. Among non-destructive methods, electronic nose technology using metal oxide semiconductor gas sensors is a promising approach for estimating the protein and fat content of milk [8]. In addition, a miniaturized near-infrared (NIR) spectrometer can be used for on-site contactless analysis of milk components without the need for any chemical sample preparations. By using automated chemometric methods, data can be presented within a few seconds [9]. Despite these innovative techniques for assessing and screening milk, there is still a need to develop non-destructive measurement methods that are suitable for monitoring the rheological behavior of milk products, for instance. This would enable the development of in-line and real-time process monitoring and control systems.

During the analysis of the various behavior materials present when exposed to an electric or electromagnetic field, we usually determine their dielectric properties. When a material interacts with an electric or electromagnetic field E , it can cause a charge movement or dipole rearrangement in the material, depending on its composition and structure [10]. The extent of this is characterized by the so-called electric (dielectric) shift (D), which being a vector quantity, has magnitude and direction too. The relationship between the electric field strength and the electric shift is given by the absolute permittivity (ϵ) of the materials:

$$\epsilon = \frac{E}{D} \quad (1)$$

Absolute permittivity is a constant that depends on the quality of the material and is in fact a measure of the extent to which the material "responds" to the electromagnetic field strength. For homogeneous, isotropic media (i.e., in which the magnitude of the different physical quantities is the same in all three directions of space), absolute permittivity can be defined as a linear scalar quantity, whereas for anisotropic materials it can be interpreted as a homogeneous linear mapping of vector-vector type, i.e., as a second-order tensor. The dielectric shift D in real materials also depends on the polarizability of the system. The relationship between the two can be written using the Clausius-Mosotti relation [11]:

$$D = \epsilon_0 E + P = \epsilon_0 (1 + \chi) E \quad (2)$$

Since the response of real materials to the electric field E is delayed in time, the dielectric shift D is also delayed, which can be understood as a kind of phase shift (δ). The magnitude of the phase and the phase itself can only be expressed in exact terms by complex numbers, so it is useful to express the permittivity of a given medium or material as a complex function of the frequency of the applied electromagnetic field, where ϵ^* is the complex permittivity:

$$\epsilon \rightarrow \epsilon^*(f) \quad (5)$$

Just like any other complex functions, the complex permittivity can also be separated to its real and imaginary part:

$$\epsilon^*(f) = \epsilon'(f) - i \epsilon''(f); i = \sqrt{-1} \quad (6)$$

The real part of the function is called the dielectric constant (ϵ'), while the complex part is called the dielectric loss factor (ϵ''). As can be seen from the equation above, these two quantities are frequency dependent, i.e., for a given material their values vary as a

function of frequency. From an electrodynamic point of view, the dielectric constant indicates how much of the energy conveyed by the electromagnetic field can be absorbed and stored by the material interacting with it, while the loss factor expresses how much of the stored electrical energy is converted into other types of energy (such as heat or kinetic energy).

The applicability of dielectric measurements in various scientific and industrial fields has long been addressed in the literature, including their implementation in a wide variety of technological processes in the food industry, with a particular focus on dairy processes. In a 2014 study, Zhu et al. investigated the frequency and temperature dependence of the dielectric behavior of raw cow milk and goat milk for the optimization of a microwave heat treatment process. Based on the analysis of dielectric constant, loss factor and penetration depth, they concluded that the loss factor decreased with increasing temperature at a frequency of 2.45 GHz, i.e., a more homogeneous temperature profile can be achieved with microwave irradiation at this frequency over a higher temperature range [12]. In a 2018 study, Muñoz et al. investigated the dielectric parameters of distinct types of milk (raw, skimmed and condensed fat-free) when heated to ultra-high temperatures at frequencies between 10 and 2450 MHz. The research results showed that the dielectric parameters (ϵ' and ϵ'') of cow's milk at temperature above 100 °C need to be investigated in order to evaluate the sterilization of milk based on dielectric heating [13]. It was found that the dielectric constant (ϵ') decreased with frequency at all temperatures, but increased with temperature at low frequencies and decreased with temperature at high frequencies. The dielectric loss factor (ϵ'') decreased with frequency and increased with temperature over almost the entire frequency range. In a 2018 study, the fermentation process of yoghurt was monitored by measuring changes in the dielectric properties of the raw material at frequencies between 10 and 3000 MHz. The results have revealed that the dielectric loss factor of yoghurt showed a positive correlation with fermentation time, with irregular changes only at the end point of fermentation (7 hours). The dielectric constant showed a correlation with the pH and titratable acidity of the yoghurt, but only at a low frequency of 10 MHz [14]. Guo et al. in a recent study investigated the dielectric properties of milk to develop a microwave continuous-flow milk sterilization apparatus and found correlation between the dielectric constant of milk and the covariance of the heating field temperature [15].

Monitoring methods using dielectric measurements enable the development of low-cost, chemical-free, and non-destructive in-process monitoring methods to determine both the rapid detection of microbial degradation processes and the efficiency and optimal time requirements of the coagulation process. Low-power dielectric measurements do not interfere with microbial and physicochemical processes in biological materials. Further research may also allow dielectric monitoring of these processes through packaging, where the product does not become waste during testing.

Some studies have investigated the correlation between dielectric and rheological properties in certain food materials [16–18], however despite the extensive research on milk coagulation, a comparative study of enzyme-induced and acid coagulation using dielectric and rheological measurements is still needed to gain a deeper understanding of the differences between these two coagulation mechanisms and their impact on the physical properties of milk.

In this study, we aim to investigate the enzyme-induced and acid coagulation of milk by measuring the dielectric and rheological properties of milk samples during these two processes. By conducting a systematic comparison of the coagulation mechanisms, we seek to explain the differences in the evolution of the protein network structure, the impact on the electrical properties of milk, and the changes in rheological behavior.

2. Materials and Methods

In our research, we investigated the coagulation process of raw milk samples by two different methods: enzyme-induced and acidic coagulation. During both type of

coagulation, the dielectric behavior and the apparent viscosity of the milk samples were simultaneously monitored. The measurements were performed in three parallel replicates.

The milk sample was originated from a local cattle farming facility. Prior to the experiments, the samples were tested for somatic cell count (SCC), which was found to be around 110.000 cells/mL, therefore the possibility of mastitis was ruled out. The initial pH of the sample was 6.50 ± 0.05 . For the enzyme-induced coagulation, 250 mL of milk sample was being used, with an addition of MAXIREN 600 (DSM Food Netherlands, chymosin originated from *Kluyveromyces lactis*, 600 IMCU/mL) enzyme in a concentration of 4.5 µl/100 ml. The enzyme concentration was chosen in accordance with the manufacturer's standard recommendations. For the acid coagulation process, the same amount of milk was used, with an addition of industrial thermophile yogurt culture (*Lactobacillus delbrueckii* subsp. and *Streptococcus thermophilus*). The dosing concentration of the freeze-dried culture in the inoculated milk volume was within the recommended dosing range of 0.03 g/100 ml for industrial technology applications.

During the two coagulation processes the inoculated milk samples were kept under a constant 40 ± 1.5 °C temperature – this range falls within the optimal range for both the applied enzyme and the bacterial culture as well. To maintain the inoculation temperature, the sample containers were placed in a water bath (Medline BS-11).

The investigation of the dielectric behavior covered the measurement of the dielectric constant (ϵ') every 5 minutes in the first 30 minutes of the experiment, and afterwards, every 10 minutes. These parameters were determined by using a DAK (dielectric assessment kit) type 3.5 (SPEAG GmBh) with an open-ended dielectric sensor connected to a vector network analyzer (VNA, type ZVL-3, Rhode&Schwarz GmBh) with a 50 Ohm coaxial power supply line at a frequency range of 200-2400 MHz. The values of the dielectric properties as a function of frequency are obtained from the average of 3-3 measurements at 10 different points, and the arithmetic mean of these measurements is used to determine the values of the investigated parameters associated with a given measurement point.

The change in viscosity during milk coagulation was monitored using an SV-10 vibro viscometer (A&D Company, Japan). The principle of the measurement is that the two thin metal plates of the instrument are vibrated by electromagnetic forces, which, when immersed in the material to be measured, cause a change in vibration. In the case of milk and other colloidal systems, we can measure apparent viscosity, which is always determined by the measurement circumstances. The determination of change in viscosity also took place every 5 minutes in the first phase (0-30 minutes), and 10 minutes afterwards (30-60 minutes). The schematics of the experimental setup can be observed in Figure 1.




Figure 1. Experimental arrangement (from left to right: dielectric assessment kit, VNA, dielectric sensor submerged in the milk sample, viscometer probe, viscometer unit).

3. Results and discussion

In the first part of the experiments, we analyzed the dielectric and rheological behavior of raw milk samples when undergo enzyme-induced coagulation, and the correlation between the changes in dielectric parameters and apparent viscosity was investigated. Our preliminary results show that the change of dielectric parameters was higher at lower

frequencies, therefore, the dielectric constant was depicted at the frequency of 400 MHz. Figure 2 shows the variation of the investigated characteristics in the function of time.





Figure 2. Change in apparent viscosity (η) and dielectric constant (ϵ' , $f=400$ MHz) versus time during the enzyme-induced coagulation of raw milk

Based on the experimental data gathered it can be observed that the enzyme-induced coagulation of milk follows a similar trend for both the change in apparent viscosity and the change in dielectric constant as a function of time. During the initial phase, both viscosity and dielectric constant remain relatively constant, which indicates that the coagulation process is in its initial stages, with the enzyme slowly breaking down the milk proteins and the formation of the protein network just beginning. Starting from 10 minutes, both the viscosity and the dielectric constant shows a rapid increase in their values. This suggests that the coagulation process is accelerating, and the protein network is forming at a faster rate. The κ -casein protein, which provides stability to the casein micelle, is being hydrolyzed by the enzyme, result in the formation of a glucomacropetide and a para- κ -casein fraction released into the whey [19]. This means that the steric repulsion ceases between the hydrophobic para-casein micelles due to their lack of negative surface charge and they begin to bind together. The increase in viscosity is attributed to the formation of a more substantial and rigid network of proteins, which slows down the flow of the liquid. Similarly, the rapid increase in dielectric constant is due to the formation of a more complex and continuous network of proteins which can absorb and store the electromagnetic energy better. In the study of Li et al. concluded that the dielectric parameters of proteins are influenced by their structural changes and the change of the interaction between the proteins and surrounding medium [20]. Around 25 minutes, the dielectric constant reaches its maximum value, while the apparent viscosity marks its highest point at 30 minutes. Afterwards, both become relatively constant, with a slight decrease observable in both of them, which might be due to the syneresis of the clot. This indicates that the coagulation process has reached its completion with the protein network being fully formed, i.e., the point of clot solidification occurs. With this stable state, no observable physicochemical changes take place anymore, which results in no significant changes in the dielectric properties as well (Figure 2). The pH of the sample during the final / stationary phase was measured to be 6.0 ± 0.05 .

The alteration or modification of casein micelles can occur, of course, due to other factors or treatment processes too. In a 2021 study Blinov et al. showed that the coagulation of casein micelles can happen under the action of Zn^{2+} ions originated from organic chelated Zinc compounds [21], while others reported that different pre-treatments methods, such as ultrasonication [22], high pressure and/or thermal treatments [23, 24] can significantly affect (accelerate the process, or making the aggregates bigger, for example) the aggregation of the micelles. These molecular-level processes can be investigated or monitored through different analytical methods, such as photon correlation spectroscopy [21], small deformation rheology [22], gel permeation chromatography or HPLC [23], but it is worth mentioning that sol-gel transformation and coagulation mechanisms can be precisely analyzed by dielectric measurements as well [25]. Since the aggregation process of casein micelles has not yet been extensively investigated by dielectric measurements, and comparative analysis of rheological and dielectric properties has not been carried out at all, the method we applied is positively worth investigating – especially because of the numerous advantages of dielectric assessment (low costs, non-damaging, requiring no sample preparation, etc.) over the aforementioned analytical methods.

To determine the correlation between the changes in viscosity and the dielectric constant, we established a logarithmic-transformed linearized function between these two values, i.e., depicted the dielectric behavior in the function of the parameter that describes the change in material structure (viscosity). By this method, we can analyze whether the structural change is also reflected in the change of the dielectric behavior. Since the time-dependent dynamics of the whole process can be split into two distinct phases (10-25 minutes, 30-60 minutes), and because there is a slight shift between the maximum point of the dielectric constant and the apparent viscosity (25 mins vs 30 mins), we depicted these phases separately (in the first 10 minutes, no observable difference is shown the values of viscosity, therefore the correlation analysis is not applicable). Figure 3a shows the data obtained for the 10-25 minutes interval, and Figure 3b for the 30-60 minutes interval (second phase of coagulation).






Figure 3. Correlation between the apparent viscosity (η) and the dielectric constant (ϵ') during 10-25 minutes (a) and 30-60 minutes (b) of the enzyme-induced coagulation process.

Based upon the values of the coefficient of determination calculated for each phase of the coagulation process ($R^2 = 0,9655$ and $0,922$, respectively), it can be stated that there is a strong correlation between the apparent viscosity of the inoculated milk sample and its dielectric behavior. On one hand, this indicates that the measurement of the dielectric constant can be used to predict or verify the point of clot formation, even in industrial scale. The use of measurement methods based on dielectric properties can be advantageous to the measurement of viscosity in more than one way, e.g. it does not alter or brake the structure of the investigated material, is easier to automatize, using multiple sensors is more easily implemented, and the obtained values are basically independent from the measurement circumstances (except for temperature, of course). On the other hand, these experimental findings strongly support the idea that the chemical, biochemical and physical processes which involve the transformation of molecular components can be monitored by measuring the dielectric behavior of the investigated media, since the dielectric properties – aside from the temperature and the frequency – mostly depend on the physical and (bio)chemical structure and composition of the materials. Kumar et al. studied the viscosity and dielectric properties of edible oils and concluded that the strong correlation of viscosity with dielectric loss tangent enable of assessing the quality of oils based on the analysis of dielectric behavior [26].

In the second part of our experiments, we investigated the acid coagulation of the raw milk sample originated from the same place. The main distinct difference between the two processes is that during acid coagulation, the applied microbial strains (*Lactobacillus delbrueckii* and *Streptococcus thermophilus* in our case) break down the lactose content of the sample, converting it into lactic acid, which lowers the pH of the medium. When the pH reaches the isoelectric point of the casein micelles ($\text{pH}=4.5\text{--}4.6$), the net surface charge becomes zero, and therefore the electrostatic repulsion no longer persists, which will eventually cause the casein micelles to aggregate [27]. As in the previous series of experiments, firstly we investigated the dynamics of the apparent viscosity and dielectric constant of the fermentation process in the function of time.




Figure 4. Change in apparent viscosity (η) and dielectric constant (ϵ' , $f=400$ MHz) versus time during the acid coagulation of raw milk

Since the mechanism of this type of aggregation is different on a molecular level compared to the enzyme-induced process, the values, and the variation of viscosity over time show observable differences, as can be seen on Figure 4. One of the most prominent differences can be found in the order of magnitude of values: compared to the enzyme-induced samples, the highest level of viscosity exceeds 48 mPa·s, whereas in the case of the former process, the maximum value resides around 460 mPa·s. From a technological point of view this is perfectly reasonable of course; enzyme-induced coagulation is applied during cheese production, while acid coagulation is used in yogurt manufacturing. Differences however can be found in trends of change as well. In the first phase (0-55 minutes) a slight increase can be detected, which is followed by a steep raise up to the maximum value of viscosity (55-95 minutes). This indicates that during acid coagulation, to reach the point of clot solidification takes considerably more amount of time than that of the enzyme-induced.

The dielectric constant also acts differently compared to the former process. In the first phase, a slight decrease can be observed, which is then followed by a steeper, characteristic drop in values. These reflections can be explained by the molecular mechanism that happens during the acid coagulation. In the first 55-60 minutes, bacteria continuously convert lactose into lactic acid, which reduces the electrical susceptibility of the medium, since lactose molecules are easier to polarize than lactic acid. Liu et al. also verified that the presence and concentration of lactose has no effect on the change trends of dielectric constant but affect its value at a given frequency in milk [28]. Higher lactic acid concentration manifest in higher dielectric constant in aqueous system [29], but in multicomponent systems, such as the milk, the fat and content and the structural changes of protein molecules also determined the dielectric behavior. The increasing presence of lactic acid progressively decreases the pH, and when it falls below pH=5, the destabilization of casein micelles takes place. When the pH ultimately reaches the isoelectric point of casein micelles, the aggregation (i.e., the formation of protein network) begins. In our case, the pH of the sample decreased from its initial 6.5 ± 0.05 value down to 4.5 ± 0.03 . This type of sol-gel transformation in terms of dielectric behavior is manifested in the fact that, on the one hand, the casein aggregates (and then chains) increasing in size reduce the electrical susceptibility of the basic material matrix due to their molecular structure and stability [30],

i.e. they “respond” to the electromagnetic field strength to a lesser and lesser extent. This leads to a decrease in the rate of energy absorption and energy storage capacity [31], (characterized by a decrease in the dielectric constant. On the other hand, as the casein micelles destabilize, the average micelle concentration of the medium decreases, which in turn reduces the conductivity of the material – the specific conduction loss thus becomes smaller as the process progresses. The charge of the protein’s surface also affects the extent of the dielectric constant, therefore, as the casein micelles have lost their net surface charge prior to the destabilization phase, can also contribute to the decrease of dielectric constant [32].

To determine the connection and correlation between the rheological and dielectric characteristics, we used the same method discussed earlier during the enzyme-induced coagulation, i.e., establishing a logarithmic-transformed linearized function of the values. Since the acid coagulation can also be divided into two clearly distinguishable phases, we plotted these functions separately too (Figure 5a, 5b).




Figure 5. Correlation between the apparent viscosity (η) and the dielectric constant (ϵ') during 0-55 minutes (a) and 60-95 minutes (b) of the acid coagulation process.

The obtained R^2 -values for the first and second phase are 0,976 and 0,967, respectively, which indicates that the correlation between the rheological properties and the dielectric behavior – just like in the case of the enzyme-induced coagulation – is straightforward. During the second phase however the slope of the curve is negative as opposed to the enzyme-induced coagulation process, which is due to the fact that in this case the viscosity and the dielectric constant acts completely opposite – whilst the former increases rapidly, the latter has a steep decrease in its values. Nonetheless, these observations suggests that regardless of the molecular mechanism that induces the clot formation, there is a clear connection between dielectric behavior and the apparent viscosity of the media, which makes the dielectric-based measurements suitable for the monitoring of both types of processes.

4. Conclusions

In our work, we investigated the enzyme-induced and acid coagulation of raw milk samples, and these processes are monitored by measuring the changes in apparent viscosity, and the dielectric constant of the fermentation media. Our results revealed that both the enzyme-induced and the acid coagulation process can be divided into two distinct phases in terms of dielectric ($f=400$ MHz) and rheological behavior, however the tendencies of these phases differ from each other due to the fundamental molecular differences in the two coagulation mechanisms. In case of the enzyme-induced aggregation, during the first 10 minutes neither the apparent viscosity nor the dielectric constant shows any observable change. After that, in the period of 10-30 minutes, the dielectric constant and the apparent viscosity presents a steep increase and reaches their respective maximum value. This indicates that the point of clot solidification occurs roughly half an hour after the enzyme is added to the system. In case of the acid coagulation, the solidification takes considerably more time, and in the first phase of the process, a slight increase in viscosity, and a slight decrease in the dielectric constant can be observed. Afterwards, around 50-55 minutes, when the destabilization phase finishes, a steep increment can be seen in the values of apparent viscosity, and a sharp decrease in the dielectric constant.

To determine whether the dielectric behavior and the physicochemical structure (represented by the viscosity) correlate, we constructed linearized functions for the two distinct phases of the investigated coagulation processes, i.e., plotted the 10-based log values of the dielectric constant in the function of $\log(\eta)$. Based on the obtained R^2 -values (0,9655 and 0,9767 for the first and second phase of the enzyme-induced process, and 0,992 and 0,9676 for the acid coagulation process) our results suggest that regardless of the molecular mechanisms that induces the coagulation itself, there is a strong correlation between the values of apparent viscosity and the dielectric constant, therefore making the dielectric measurement as a suitable alternative for monitoring technique in dairy processing.

Author Contributions: Conceptualization, S.B. and Z.J.; methodology, S.B., J.C and Z.J.; investigation, R.D.; data curation, S.B. and J.Z.; writing—original draft preparation, R.D. and Z.J.; writing—review and editing, S.B.; visualization, R.D, J.C.; supervision, S.B.; funding acquisition, S.B., Z.J. and R.D. All authors have read and agreed to the published version of the manuscript.

Funding: The authors are grateful for the financial support provided by the New National Excellence Program, under project numbers, UNKP-22-2-SZTE-199, UNKP-22-5-SZTE-208 and UNKP-22-3-SZTE-204. This project was supported by Bolyai János Research Scholarship of the Hungarian Academy of Sciences (BO/00161/21/4).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Research data is available on special request.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Freitas, C.; Silva, M.; Oliveira, J.P.B.; da Silva, F.B.; Ramos, M.B.; de Sousa, J. Study of milk coagulation induced by chymosin using atomic force microscopy. *Food Bioscience* **2019**, *29*, 81–85. 10.1016/j.fbio.2019.04.003.
2. Slaćanac, V.; Novaković, P.; Petrak, T.; Kordić, J. Application of mathematical models in milk coagulation process during lactic acid fermentation. Part I. Relation between enzymatic and acidic milk coagulation. *Acta Alimentaria* **2000**, *29*, 241–254. 10.1556/AAlim.29.2000.3.4.
3. Ben Amira, A.; Besbes, S.; Attia, H.; Blecker, C. Milk-clotting properties of plant rennets and their enzymatic, rheological, and sensory role in cheese making: A review. *International Journal of Food Properties* **2017**, *20*, S76–S93.
4. Teseme, W.B.; Weldelesassie, H.W. Review on the study of dielectric properties of food materials. *American Journal of Engineering and Technology Management* **2020**, *5*, 76–83.
5. Zhu, X.; Guo, W.; Jia, Y.; Kang, F. Dielectric properties of raw milk as functions of protein content and temperature. *Food and bioprocess technology* **2015**, *8*, 670–680.
6. Lucey, J.A. Formation, structural properties, and rheology of acid-coagulated milk gels. In *Cheese*; Elsevier: 2017; pp. 179–197.
7. Blinov, A.V.; Siddiqui, S.A.; Blinova, A.A.; Khramtsov, A.G.; Oboturova, N.P.; Nagdalian, A.A.; Simonov, A.N.; Ibrahim, S.A. Analysis of the dispersed composition of milk using photon correlation spectroscopy. *Journal of Food Composition and Analysis* **2022**, *108*, doi:10.1016/j.jfca.2022.104414.
8. Mu, F.; Gu, Y.; Zhang, J.; Zhang, L. Milk Source Identification and Milk Quality Estimation Using an Electronic Nose and Machine Learning Techniques. *Sensors* **2020**, *20*, doi:10.3390/s20154238.
9. Risoluti, R.; Gullifa, G.; Materazi, S. Assessing the Quality of Milk Using a Multicomponent Analytical Platform MicroNIR/Chemometric. *Frontiers in Chemistry* **2020**, *8*, doi:10.3389/fchem.2020.614718.
10. Baker-Jarvis J, Kim S. The Interaction of Radio-Frequency Fields With Dielectric Materials at Macroscopic to Mesoscopic Scales. *Journal of Research of National Institutes of Standards and Technology*. **2012**, 117:1–60. doi: 10.6028/jres.117.001.
11. Talebian, E.; Talebian, M. A general review on the derivation of Clausius–Mossotti relation. *Optik* **2013**, *124*, 2324–2326.
12. Zhu, X.; Guo, W.; Jia, Y. Temperature-dependent dielectric properties of raw cow's and goat's milk from 10 to 4,500 MHz relevant to radio-frequency and microwave pasteurization process. *Food and Bioprocess Technology* **2014**, *7*, 1830–1839.
13. Muñoz, I.; Gou, P.; Picouet, P.A.; Barlabé, A.; Felipe, X. Dielectric properties of milk during ultra-heat treatment. *Journal of Food Engineering* **2018**, *219*, 137–146.
14. Guo, C.; Xin, L.; Dong, Y.; Zhang, X.; Wang, X.; Fu, H.; Wang, Y. Dielectric properties of yogurt for online monitoring of fermentation process. *Food and bioprocess technology* **2018**, *11*, 1096–1100.
15. Guo, J.; Zhu, H.; Yang, Y.; Guo, Q. Continuous-Flow Microwave Milk Sterilisation System Based on a Coaxial Slot Radiator. *Foods* **2023**, *12*, 459. <https://doi.org/10.3390/foods12030459>
16. Cui, L.; Chen, J.; Zhai, J.; Peng, L.; Hayes, D.G. Oil Penetration of Batter-Breaded Fish Nuggets during Deep-Fat Frying: Effect of Frying Oils. *Foods* **2022**, *11*, 3369. <https://doi.org/10.3390/foods11213369>
17. Ahmed, J.; Prabhu, S.; Raghavan, G.; Ngadi, M. Physico-chemical, rheological, calorimetric and dielectric behavior of selected Indian honey. *Journal of Food Engineering* **2007**, *79*, 1207–1213.
18. Ahmed, J.; Thomas, L.; Khashawi, R. Influence of hot-air drying and freeze-drying on functional, rheological, structural and dielectric properties of green banana flour and dispersions. *Food Hydrocolloids* **2020**, *99*, 105331.
19. Salvador D, Acosta Y, Zamora A, Castillo M. Rennet-Induced Casein Micelle Aggregation Models: A Review. *Foods*. **2022**, *11*(9):1243. doi: 10.3390/foods11091243.
20. Lin, L.; Chuan, L.; Zhe, Z.; Emil, A. On the 'Dielectric "Constant" of Proteins: Smooth Dielectric Function for Macromolecular Modeling and Its Implementation in DelPhi. *Journal of Chemical Theory and Computation*. **2013**, *9*(4). 2126–2136. 10.1021/ct400065j.
21. Blinov, A.V.; Siddiqui, S.A.; Nagdalian, A.A.; Blinova, A.A.; Gvozdenko, A.A.; Raffa, V.V.; Oboturova, N.P.; Golik, A.B.; Maglakelidze, D.G.; Ibrahim, S.A. Investigation of the influence of Zinc-containing compounds on the components of the colloidal phase of milk. *Arabian Journal of Chemistry* **2021**, *14*, 103229, doi:<https://doi.org/10.1016/j.arabjc.2021.103229>.
22. Gregersen, S.B.; Wiking, L.; Hammershøj, M. Acceleration of acid gel formation by high intensity ultrasound is linked to whey protein denaturation and formation of functional milk fat globule-protein complexes. *Journal of Food Engineering* **2019**, *254*, 17–24, doi:<https://doi.org/10.1016/j.jfoodeng.2019.03.004>.
23. Law, A.J.R.; Leaver, J.; Felipe, X.; Ferragut, V.; Pla, R.; Guamis, B. Comparison of the Effects of High Pressure and Thermal Treatments on the Casein Micelles in Goat's Milk. *Journal of Agricultural and Food Chemistry* **1998**, *46*, 2523–2530, doi:10.1021/jf970904c.
24. Hovjecki, M.; Miloradovic, Z.; Rac, V.; Pudja, P.; Miocinovic, J. Influence of heat treatment of goat milk on casein micelle size, rheological and textural properties of acid gels and set type yoghurts. *Journal of Texture Studies* **2020**, *51*, 680–687, doi:<https://doi.org/10.1111/jtxs.12524>.
25. Mortadi, A.; Chahid, E.G.; Nasrellah, H.; Cherkaoui, O.; El Moznine, R. Dielectric and electric properties as a tool to investigate the coagulation mechanism during sludge treatment. *Environmental Technology* **2019**, *40*, 72–85, doi:10.1080/09593330.2017.1378927.

26. Kumar D, Singh A, Tarsikka PS. Interrelationship between viscosity and electrical properties for edible oils. *Journal of Food Science and Technology* **2013**;50(3), 549-54. doi: 10.1007/s13197-011-0346-8. 444
27. Sinaga, H., Bansal, N., Bhandari, B. Effects of milk pH alteration on casein micelle size and gelation properties of milk, *International Journal of Food Properties* **2017** 20(1), 179-197, doi: 10.1080/10942912.2016.1152480 445
28. Liu, Q., Guo, W., Zhu, X. Effect of lactose content on dielectric properties of whole milk and skim milk. *International Journal of Food Science & Technology* **2018** 53, 2037-2044, doi:10.1111/ijfs.13790. 446
29. Eldamak AR, Thorson S, Fear EC. Study of the Dielectric Properties of Artificial Sweat Mixtures at Microwave Frequencies. *Biosensors* **2020** 10(6):62. doi: 10.3390/bios10060062. 447
30. Harindran, A.; Madhurima, V. On the efficacy of dielectric spectroscopy in the identification of onset of the various stages in lactic acid coagulation of milk. *Journal of Microwave Power and Electromagnetic Energy* **2020**, 54, 161-181, doi:10.1080/08327823.2020.1755484. 448
31. Tıraş, B.; Dede, S.; Altay, F. Dielectric Properties of Foods. *Turkish Journal of Agriculture - Food Science and Technology* **2019**, 7, 1805-1816, doi:10.24925/turjaf.v7i11.1805-1816.2650. 449
32. Henningsson, M.; Ostergren, K.; Dejmek, P.; Ostergren, K. The electrical conductivity of milk - The effect of dilution and temperature. *Int J Food Prop* **2005**, 8, 15-22, doi:Doi 10.1081/Jfp-200048143. 450

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content. 451